

DB105

DB105 6W/940 1000lm DALI 60° white GST18i5bl

ARTICLE CODE
2510D-00008-23-W5D

downlight



Recessed spots such as the DB105 provide focused, functional lighting. At 6W this model delivers 1000lm (139lm/W) in neutral white light (4000K). Colour consistency: SDCM2. The 60° beam provides focused lighting. The cut-out measures Ø105mm, the outer diameter is Ø115mm. The housing is aluminium with a white finish and a polycarbonate cover and weighs 0.6kg, rated IP20/IK03. Dimmable (DALI). The LED lasts 66,000 hours (L90B10). Manufactured in the Netherlands, with a 5-year warranty.

POWER

6 W

EFFICIENCY

139 lm/W

COLOUR · CRI

4000K · 90

LIGHT

System efficiency (lm/W)	139
Colour temperature	4000K
Colour rendering (CRI)	90
SDCM	2
Beam angle	60°
UGR	19
Service life	66.000h/L90B10

ELECTRICAL

System power (W)	6
LED power	940
Supply voltage	220..240V
Frequency	50..60Hz
Driver	DALI
Dimmable	yes
Dim type	continuous
Quantity per B16	34
Energy class (EU)	D
Warranty (year)	5

MECHANICAL

Housing	aluminium · white
Cover	polycarbonate
Type	downlight
Mounting	recessed
Protection rating	IP20
Impact rating	IK03
Connection	GST18i5b
Adjustable	no

ALSO AVAILABLE WITH

DRIVERS

DALI

on/off

COLOUR TEMPERATURE

4000K


3000K

HOUSING

white

black

DIMENSIONAL DRAWING



Lixero B.V. · lixero.eu

The value depends on the selected configuration and setting of the product.
All nominal values at an ambient temperature of 25 °C.
Electrical and photometric values have a tolerance of 10%.
Specifications subject to change without prior notice.